

WinTool Interface for SolidCAM

Release Notes

Version 3.5.0

- ✓ Compatible with WinTool 2022.2.0
- ✓ Bugfix DXF generation for Thru Hole Taps with a tip angle of 180°
- ✓ Bugfix missing Thread Parameters for Thread Mills
- ✓ Bugfix feed per tooth calculation for drills
- ✓ Bugfix mirrored inserts when transferring turning tools
- ✓ Bugfix exporting some tools throwing System.Collections.Generic.KeyNotFoundException
- ✓ Move Exchange, UserModels and Sample Data folders to Public Documents\WT-SolidCAM-Interface
- ✓ Improved Setup
- ✓ Embed release notes into setup
 - Added shortcut to start menu
- ✓ Bugfix for broken start menu shortcut to the manual
- ✓ Extend manual with troubleshooting for not working "PUT" button
- ✓ Updated chapter Tool List export in the manual

Version 3.4.1

- ✓ Bugfix for an error that prevents export of turning tool

Version 3.4

- ✓ Compatible with WinTool 2022.1.0
- ✓ Compatible with SolidCAM 2022
- ✓ Ensured compatibility with WinTool Versions older than 2020.3.1
- ✓ Corrected writing of holder contours
- ✓ Thread Mills Cutting Length is now correctly calculated
- ✓ Improved Import of Cutting Conditions

Version 3.3

- ✓ Compatible with WinTool 2021.2.0
- ✓ Compatible with SolidCAM 2021
- ✓ Coolant Import improvement
- ✓ New configuration option "RoughActive"
- ✓ Added Pitch and Helical Angle to Tool Import

Version 3.2

- ✓ Compatible with WinTool 2021.1.3
- ✓ Coolants are now configurable such as in SolidCAM
- ✓ Cutting Conditions now have a Configuration option for an Import with the WinTool or the SolidCAM definitions
- ✓ Added new configuration option "UseShapeImport"

Version 3.1

- ✓ Compatible with WinTool 2021.1
- ✓ Turning Tools holder rotation improvement

Version 3.0

- ✓ Compatible with SolidCAM 2021
- ✓ Turning Tool Import optimization
- ✓ Implementation of the new 3D Export (Automatic Export of .STL files and conversion of .STEP to .STL)

Version 2.1.1

- ✓ Compatible with WinTool 2020.3.1
- ✓ Cutting Conditions Import optimization when selecting a Single Cutting Condition

Version 2.1

- ✓ Compatible with WinTool 2020.3
- ✓ General Tool Import optimization
- ✓ Cutting Conditions Import optimization

Version 2.0

- ✓ Compatible with WinTool 2019.1
- ✓ Additionally compatible with SolidCAM 2020-1
- ✓ Inch Tools are now correctly imported
- ✓ Conical transition from mill to the shank is now correctly displayed
- ✓ New configuration option "Description"
- ✓ Improvement on the Import of Cutting Conditions
- ✓ Improvement on Coolant support:
 - ✓ New configuration option "Coolant0-Coolant9"
- ✓ New flexible License system
- ✓ Support of Turning Tools:
 - Tool type "Internal turning/InternalGeneral" (/SC30) added
 - Tool type "External turning/ExternalGeneral" (/SC31) added
 - Tool type "Internal grooving/InternalGrooving" (/SC32) added
 - Tool type "External grooving/ExternalGrooving" (/SC33) added
 - Tool type "Internal threading/InternalThreading" (/SC34) added
 - Tool type "External threading/ExternalThreading" (/SC35) added

Version 1.12

- ✓ Additionally compatible with SolidCAM 2018.
- ✓ MakeList 3.11.0 added
 - MakeList now supports file versions 2.3
 - Optional support of several D and H values
- ✓ WinTool Tool export changes:
 - Shows the assembly state of the tools in the selection list
 - Display of available tool duplicates in the CAM tool selection

Version 1.11

- ✓ Additionally compatible with SolidCAM 2016.

Version 1.10

- ✓ Additionally compatible with SolidCAM 2015.
- ✓ Adjustment on the face mill import
- ✓ Corrections on the post-processor for list export
- ✓ Correction during import of thread mills: number of teeth and gradient

Version 1.9

- ✓ Additionally compatible with SolidCAM 2014
- ✓ Tool type "Probe/measuring probe" (/SC19) added
- ✓ Correction during import of tool assembly holders

Version 1.8

- ✓ Compatible with *WinTool* 2011-2014
- ✓ Import as custom tool when User model enabled or contour DXF defined
- ✓ Corrections during import of the shoulder length during milling
- ✓ Correction during import of the taper mill angle with the face mill type
- ✓ Latest version of WT-MakeList version integrated, for details, see WT-MakeList Manual
- ✓ Latest version of WT-ToolExport integrated:
 - ✓ Selection of the filter "Preferred only" is saved
 - ✓ Better readability with high DPI settings
 - ✓ Compatible with *WinTool* 2014
- ✓ Individual tool import: ID no. is imported as NC number if "T-No=Ident No" is enabled in the machine assigned and T-number = 0.

Version 1.7

- ✓ Compatible with *WinTool* 2013, 2012 and 2011
- ✓ Compatible with SolidCAM 2013, 2012, 2011 and InventorCAM 2013
- ✓ Option for defining a special contour for each tool assembly (page **Fehler! Textmarke nicht definiert.**)
- ✓ Latest version of WT-MakeList integrated. For details, see WT-MakeList-Manual

Version 1.6

- ✓ Compatible with *WinTool* 2012 and SolidCAM 2012
- ✓ Corrections during import of taper mill, slot mill, dove tail mill, chamfer drill
- ✓ Adjustment during import of the tool parameter "shaft diameter"
- ✓ Support of the tool parameters "shoulder diameter" and "start shoulder length"
- ✓ Latest version of WT-ToolExport integrated:
 - ✓ Height of search window adjustable
 - ✓ Compatible with *WinTool* 2012

Version 1.5

- ✓ Compatible with *WinTool* 2011 and SolidCAM 2011
- ✓ Latest versions of WT-ToolExport and WTMakeList integrated
- ✓ New tool type "Ignore" (/SC00) added
- ✓ Improved troubleshooting

Version 1.4.3

- ✓ Installation of the interface via set-up programme
- ✓ New: WinTool 2010 must have been started when interface is used
- ✓ New WT-ToolExport module integrated
- ✓ WT-MakeList version 3.7 integrated
- ✓ Interface settings can now be configured via window
- ✓ Support of CAPTO recordings
- ✓ Type taper mill (/SC06) is imported correctly
- ✓ Holder component of a tool assembly is determined automatically if not available

- ✓ New cutting condition import process (if setting SelectCutData is enabled)
- ✓ Improved processing of class configuration

Version 1.4.2

- ✓ New field "UseDxfShapeCutting" added to csv. The value is fixed to "1".
- ✓ SolidCAM integration added

Version 1.4.1

- ✓ Compatible with *WinTool 2009* and *WinTool 2010*

Version 1.4

- ✓ Fields "Description" and "Message1-5" in the csv are filled with WinTool fields Descript, Design, OldName, MSign, ReplacedBy and MDate.
- ✓ Splitpoint is generally set to 0.
- ✓ "FType" is set to "F". Base value for "Feed" fields is F from the cutting condition. For the types CENTER DRILL, SPOT DRILL, DRILL, CHAMFER_DRILL, TAP, REAMER, BORE, "FeedZ" and "FeedZPenetration" will not be divided in half.
- ✓ The *WinTool* tool assembly number in the format "#KWZNR" is appended to "ToolName" and "HolderName".
- ✓ "ToolUserType" is filled with the class name of the tool assembly.

Version 1.3.1

- ✓ Correct handling of "Splittpoint"
- ✓ Cutting condition data selectable

Version 1.3

- ✓ #2140: Change ToolTypes according to Spec of SC (Schumacher, RK, 07/09/09)
(SC09: ENGRAVING TOOL is not the right tool type (Illig, RK, 24/07/09))
- ✓ #2141: Parameter "/M 1" generates a .csv with a line that is there twice. (OB, 01/09/09)

Version 1.2

- ✓ #2038: SC15: Calculate ShoulderLength (Illig, 17/07/09)
- ✓ #2039, #2040, #2041, #2042: Change of the tool types:
BALL-NOSED → BALL NOSE MILL, BULL MILL → BULL NOSE MILL,
TAPER → TAPER MILL, SLOT → SLOT MILL, LOLLIPOP → LOLLIPOP MILL,
ENGRAVING → ENGRAVING TOOL, CHAMFER_DRILL → CHAMFER_DRILL

Version 1.1

- ✓ #2021: Name correction of the interface
- ✓ #2022: Use neck diameter of the name-giving component as ArborDiameter, if available (Illig, 09/07/09)
- ✓ #2023: SC05: "Angle" = 180° - E1 (Illig, 09/07/09)
- ✓ #2024: SC09: "TipDiameter" has to be greater than 0 (Illig, 09/07/09)
- ✓ #2025: SC10: "Angle" = E1 (Illig, 09/07/09)
- ✓ #2026: SC10: "TaperAngle" = E2 (Illig, 09/07/09)
- ✓ #2027: SC17: "Diameter" and "CuttingLength" added (Illig, 09/07/09)

Version 1.0.0

- ✓ First version